





Tombstone Gun Grips

PO Box 2171, White City, OR 97503
www.TombstoneGrips.com Dave@TombstoneGrips.com

Tracing Received with order

No Tracing Received with order

Thank you for your order, and for reading the “terms of sale” page which detailed exactly what is offered prior to your having clicked on “*I have read and agree... now show me the grips!*”



This page explained in detail the nature of the 90% finished Tombstone Grip kits, including the warranty terms to which you agreed before ordering.

If you sent a tracing that shows the screw hole location and the shape and size of your gun frame or existing grips, and the grip sent to you is not at least as large as the tracing, then Tombstone will pay the cost of making another grip (which can be the same or a different choice, at your option) AND the return shipping to you, upon return of the grips along with your original order number and a new tracing.

If you did NOT send a tracing or template showing the size and shape, and hole location that fits your particular gun, and the new grip does not fit your gun but does match the on-line description and dimensions provided on the order page, the grip is not returnable. (This was clearly explained in the terms of sale, and on the grip listing where you selected “No, I am not sending a tracing and I agree to be responsible...”). If the grip sent is SMALLER than the dimensions listed, or the wrong model of grip, then of course it is returnable for exchange. To assure proper size, please send...

1. An accurate tracing or template showing the size and shape of the grip, and the screw hole location.
2. Your return address and the original order number and date so I can locate the information.

To make a tracing or template...

With removable 2-panel grips, place each grip panel on a 3 x 5 inch standard index card, hold it firmly, and trace around the outline with a sharp pencil. Mark the screw hole (you can use the screw to mark the paper -- a little “Magic Marker” on the tip will transfer ink to the tracing nicely). Two accurate tracings is better than one -- helps average out small errors when used to test the new grips.

With 1-piece single action grips, remove the backstrap and the grip. Put the backstrap on the gun again, and press a 3 x 5 index card against the frame to transfer the outline, or trace around the outside of the frame with a pencil (or both). Get an accurate impression of the top of the frame, where the grip must fit. Then use a pair of scissors to carefully cut out the outlined paper and create a “paper grip” or template. This should be trimmed to fit your gun exactly as the new grip will fit it.

Take your time, get it right. This is the “blueprint” used to make your new grips. You can patch it if you cut too short.

Send Returns to:

Tombstone Gun Grips
PO Box 2171
White City, OR 97503 USA